# EVAPORATION CHARACTERISTICS OF A SOLAR IRRADIATED NATURALLY VENTILATED CLASS A PAN

# **MD. ASHIKUR RAHMAN**

PERPUSTAKAAN UNIVERSITI MALAYSIA SABAH

# THIS THESIS IS SUBMITTED TO FULFILL THE FOR CHANGING MASTER OF ENGINEERING

# FACULTY OF ENGINEERING UNIVERSITI MALAYSIA SABAH 2016



## UNIVERSITI MALAYSIA SABAH

#### BORANG PENGESAHAN STATUS TESIS

#### JUDUL: EVAPORATION CHARACTERISTICS OF A SOLAR **IRRADIATED NATURALLY VENTILATED CLASS A PAN**

#### MASTER OF ENGINEERING (MECHANICAL ENGINEERING) IJAZAH:

Sava MD. ASHIKUR RAHMAN, Sesi Pengajian 2013-2016, mengaku membenarkan tesis Doktor Falsafah ini disimpan di Perpustakaan Univesiti Malaysia Sabah dengan syarat-syarat kegunaan seperti berikut:-

- 1. Tesis ini adalah hak milik Universiti Malaysia Sabah.
- 2. Perpustakaan Universiti Malaysia Sabah dibenarkan membuat salinan untuk tujuan pengajian sahaja.
- 3. Perpustakaan dibenarkan membuat salinan tesis ini sebagai bahan pertukaran antara institusi pengajian tinggi.
- 4. Sila tandakan (/)



(Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia seperti yang termaktub di dalam AKTA RAHSIA 1972)

(Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi/badan di mana penyelidikan dijalankan)



TIDAK TERHAD

Disahkan oleh,

NURULAIN BINTI ISMAIL IBRARIAN ALAYSIA SABAH

HABAS ASSIA SEBAH

PERPUSTAKAAN

(Tandatangan Pustakawan)

ASHIKUR RAHMAN MD. MK1321007A

Tarikh: 29 Mac 2016

(Assoc. Prof. Dr. Chris Chu C ng) Penvelia



## DECLARATION

This Master of Engineering (M.Eng) thesis is an original research work. Wherever, I have taken help from the others researcher in writing the literature review, paper references are made for clarity and acknowledgement. The work was done under the guidance of a committee. The committee has three members. Associate professor **Dr. Chris Chu Chi Ming** is the chairman of this committee, at the chemical engineering program, and the other two members are **Dr. Mizanur Rahman & Dr. Noor Ajian Mohd. Lair** at Mechanical Engineering Program, Faculty of Engineering, Universiti Malaysia Sabah (UMS), 88400 Kota Kinabalu, Sabah, Malaysia.

Date: 01 April 2016

Md. Ashikur Rahman MK1321007A



## CERTIFICATION

Name : MD. ASHIKUR RAHMAN

Matric No : MK1321007A

Title : EVAPORATION CHARACTERISTICS OF A SOLAR IRRADIATED NATURALLY VENTILATED CLASS A PAN

- Degree : MASTER OF ENGINEERING (MECHANICAL ENGINEERING)
- Viva Date : 23<sup>rD</sup> FEBRUARY 2016

#### **DECLARED BY**

#### 1. Supervisor

2. Co-Supervisor

3. Co-Supervisor

Dr. Mizanur Rahman

Dr. Noor Ajian Mohd Lair

Assoc. Prof. Dr. Chris Chu Chi Ming

Signature





### ACKNOWLEDGEMENT

First and foremost, the author would like to avow the noteworthy recognizance of almighty's continual mercy and help without which no work would have been possible to accomplish the goal.

The author expresses his deepest gratitude and esteemed pleasure to the chairman of the supervisory committee **Dr. Chris Chu Chi Ming**, Associate Professor, Chemical Engineering programme, and the other two members of the supervisory committee are **Dr. Md. Mizanur Rahman & Dr. Noor Ajian Mohd. Lair**, Mechanical engineering programme, Faculty of Engineering, Universiti Malaysia Sabah (UMS), for those continuous guidance, valuable suggestion, keen instruction, distinct inspiration and advice which help me to understand and made possible to complete the thesis work successfully.

The author would like to thank Professor Dr. Rosalam Hj. Sarbatly, Dean, Faculty of Engineering, Universiti Malaysia Sabah (UMS), who give cordial help and constant encouragement towards this research works during author's study in UMS.

The author wishes to thank every staff member and all colleagues Phang, Ling, Walton at UMS for their supports and help during his study period. The author also desires to thank all friends, mainly Shaon, Mohon, Rubel, Rahman, Tusher, Ripon, Bari, Joy, Mehedi, Partho, Atif, Akash, Sagoto, Rony and Rana for their help, friendship, encouragement and moral support during author's study at UMS.

The author acknowledges the financial support donated by the Ministry of Higher Education through a fundamental grant (FRG0352) to carry out this study in Malaysia.

A deep gratitude extended to author's parents, brother and other family members for their love, time-to-time support, valuable suggestion and encouragement to continue the study. The author also acknowledges there sincere thinks of the person involved in the completion of the present thesis.

Md. Ashikur Rahman March 2016



## ABSTRACT

Evaporative water loss is of significant importance in many fields ranging from hydrology and agriculture, to food science and engineering applications. Water removal from industrial effluent streams, food processing industry and the biodiesel conversion process from microalgae is an important step in wastewater and sludge treatment, harvesting and drying of crops. The purpose of the experiment was to observe the characteristics of evaporation from class A pan and to enhance the rate of evaporation flux by using enhanced natural draft that showed Chu et al. in (2012) by installing wire mesh on the chimney to impede cold inflow. This study monitors the effect of natural draft flow enhancement on evaporation. Experiments were conducted in square shape pan at three different sizes. Dimensions of the experimental pans were side lengths 1.07m, 0.6m and 0.6m; depth 0.254m, 0.254m and 0.2m respectively. The solid wall type solar irradiated chimney was used to enhance natural draft in this research. There were two designs of solar irradiated naturally ventilated pan (SINVAP). The specification for Design-1 category SINVAP was 0.105m<sup>2</sup>, 0.28m<sup>2</sup> and 0.77m for inlet opening area, outlet opening area and solid wall chimney height respectively. The dimensions 8.65×10<sup>-3</sup> m<sup>2</sup>, 0.26m<sup>2</sup> and 1.2m were the corresponding values of Design-2 type SINVAP. A 0.64mm×0.64mm size wire mesh was installed at the outlet of the SINVAP to impede cold inflow in the SINVAP. Over about 100 days evaporation readings were taken using the different pan configurations. The experimental result showed the evaporation flux from the SINVAP with wire mesh at outlet opening was around 14% more than the open pan; in the SINVAP without wire mesh at outlet opening was lower than the open pan evaporation rate. The SINVAP evaporation flux was found to be moderately influenced by the net radiation, vapor pressure deficit and natural ventilation draft. The daily average net radiation in the SINVAP water was reduced due to reflection of incoming global radiation at the transparent plastic sheet. Reduction of net radiation in the SINVAP could have caused evaporation to be lower than open pan. The vapor pressure deficit followed the opposite trend of net radiation; as a result, the evaporation flux from the SINVAP with wire mesh has been increased. The elevated vapor deficit in the SINVAP with wire mesh could have caused evaporation to be higher than the open pan. This research found the average local wind run over the open pan was higher than the SINVAP inlet air flow. The nature of the local wind flow profile was unsteady and always fluctuated. However, the inlet air flow profile in the SINVAP was smooth, with little fluctuation. The smooth inlet air flow in the SINVAP was instrumental in transferring higher amount of water vapor molecules from the pan into the air. According to the findings of this study, the use of Chu et al., (2012) enhanced natural draft in the application fields of pond natural evaporation seems promising. The dimensions if chosen properly can thus substantially increase evaporation rates.



## ABSTRAK

#### EVAPORATION CHARACTERISTICS OF A SOLAR IRRADIATED NATURALLY VENTILATED CLASS A PAN

Kehilangan air akibat penyejatan adalah amat penting dalam pelbagai bidang yang terdiri daripada hidrologi dan pertanian, sains makanan dan aplikasi kejuruteraan. Penyingkiran air dari aliran efluen perindustrian, industri pemprosesan makanan dan proses penukaran biodiesel daripada mikroalga adalah satu langkah yang penting dalam rawatan air kumbahan dan enapcemar, penuaian dan pengeringan. Ia telah terbukti boleh dilaksanakan dalam banyak contoh. Tujuan eksperimen ini adalah untuk melihat ciri-ciri penyejatan dari pan kelas A dan peningkatan kadar penyejatan sinaran dengan menggunakan sistem pengudaraan semula jadi berasaskan matahari. Kajian ini adalah untuk memantau kesan draf semulajadi Chu et al., (2012) yang dipertingkatkan pada kadar penyejatan. Draf ini digunakan pada kajian Chu et al, Kesan aliran masuk sejuk pada ketinggian cerobong draf semula jadi menara pendingin. Kajian telah dijalankan dalam kuali berbentuk segi empat sama yang mempunyai tiga saiz yang berbeza. Menurut ujikaji pada kuali, panjang sisi kuali ialah 1.07m, 0.6m dan 0.6m dan kedalaman adalah 0.254m, 0.254m dan 0.2m. Kajian Chu et al. (2012) yang menggunakan draf semula jadi yang dipertingkatkan telah dijalankan pada kajian ini dengan menggunakan cerobong matahari yang berdinding pepejal Terdapat dua jenis reka bentuk kuali radiasi matahari dengan pengaliran udara semula jadi (SINVAP) telah digunakan. Spesifikasi reka-bentuk yang pertama kategori SINVAP adalah seperti berikut :Luas bukaan dalaman, luaran dan tinggi cerobong berdinding pepejal masing-masing adalah 0.105m², 0.28m² dan 0.77m. Spesifikasi reka-bentuk yang kedua kategori SINVAP: adalah menurut dimensi 8.65 × 10-3m<sup>2</sup>, 0.26m<sup>2</sup> dan 1.2m. Saiz jaring dawai adalah 0.64mm × 0.64mm telah digunakan pada alur keluar SINVAP. Kirakira 100 hari bacaan penyejatan diambil pada konfigurasi kuali yang berbeza. Hasil uji kaji menunjukkan kadar penyejatan dari SINVAP dengan jaring dawai pada pembukaan luaran adalah kira-kira 14% lebih daripada kuali terbuka; ia adalah rendah <del>di</del> pada SINVAP tanpa jaring dawai pada bukaan luaran. Kadar penyejatan SINVAP dipengaruhi oleh pengubahsuaian radiasi bersih, defisit tekanan wap dan draf pengudaraan semula jadi. Purata radiasi bersih harian dalam air SINVAP semakin berkurangan disebabkan oleh pantulan sinaran pada kepingan plastik telus. Penurunan radiasi bersih dalam SINVAP menyebabkan kadar penyejatan menjadi lebih rendah daripada pan terbuka. Keputusan defisit tekanan wap mengikut trend yang bertentangan dengan radiasi bersih. Hasilnya, kadar penyejatan dari SINVAP dengan dawai telah meningkat. Keputusan defisit wap meningkat pada SINVAP yang berdawai dan ini menyebabkan kadar penyejatan adalah lebih tinggi daripada pan terbuka. Keputusan kajian ini menunjukkan purata gerakan angin tempatan pada kuali terbuka adalah lebih tinggi berbanding aliran udara masuk SINVAP. Sifat profil aliran angin tempatan adalah tidak stabil dan sentiasa berubah-ubah. Walau bagaimanapun, profil aliran udara masuk di dalam SINVAP adalah licin dan stabil. Kelancaran aliran udara masuk di dalam SINVAP telah memindahkan sejumlah besar molekul wap air dari air kuali ke dalam udara.



Ramalan yang baik berkenaan dengan penyejatan oleh model penyejatan yang berbeza menunjukkan bahawa kajian Chu et al. (2012) yang menggunakan draf semula jadi yang dipertingkatkan adalah sah pada penyejatan. Menurut hasil kajian ini, penggunaan kajian Chu et al., (2012) yang menggunakan draf semulajadi jadi dalam bidang kolam penyejatan semula jadi adalah cerah. Pemilihan dimensi yang betul boleh meningkatkan kadar penyejatan dengan ketara.



# LIST OF CONTENTS

			Page
TITLE			i
DECL	ARATION	a de la compañía de l	11
CERT	IFICATION		111
	IOWLEDGEMENT		iv
ABST	RACT		v
ABST	RAK		vi
LIST	OF CONTENTS	2	viii
LIST	OF TABLES		xii
LIST	OF FIGURES		xiii
LIST	OF ABBREVIATIONS		xvii
LIST	OF SYMBOLS		xviii
LIST	OF APPENDICES		xx
CHA	PTER 1: INTRODUCTION		1
1.1	Research questions		2
1.2	Statement of research problem		2
1.3	Scope of research		3
1.4	Research objectives		4
1.5	Significance of the study		4
1.6	Research activities		5
1.7	Thesis outline		5
CHA	PTER 2: LITERATURE REVIEW		7
2.1	Research Background		7
2.2	Theory of evaporation from free surface of water	·	9
2.3	Field of natural evaporation	-=}	11
2.4	Purpose of enhancement evaporation rate		11
2.5	Pan evaporation		12
2.6	Mechanism of pan evaporation		13



2.7	Solar irra	adiated naturally ventilated pan evaporation	15
	2.7.1	Buoyancy driven movement	16
	2.7.2	Wind induced air movement	18
2.8	Cold infl	ow on natural draft	19
2.9	Influenc	e of meteorological factors on evaporation	21
	2.9.1	Solar radiation	22
	2.9.2	Wind flow	22
	2.9.3	Temperature	22
	2.9.4	Humidity	23
	2.9.5	Water height	23
2.10	Measure	ement of evaporation	23
2.11	Pan eva	aporation measurement	24
	2.11.1	Penman (1948) model	24
	2.11.2	KNF (1955) model	25
	2.11.3	Christiansen (1966) model	26
	2.11.4	Linacre (1977) model	27
	2.11.5	Thom et al. (1981) model	28
	2.11.6	Rayner (2007) model	29
2.12	Instrum	nentation of pan evaporation	29
	2.12.1	Water level measurement	30
	2.12.2	Solar radiation measurement	31
	2.12.3	Wind speed measurement	31
	2.12.4	Temperature measurement	31
	2.12.5	Humidity measurement	31
	2.12.6	Rainfall measurement	32
	2.12.7	Atmospheric pressure	32
2.13	Summa	ary of literature review	32
CHA	PTER 3:	METHODOLOGY	34
3.1	Climate	e of Site	34
3.2	Design	and construction	35
	3.2.1	Details of Class-A pan	35



	3.2.2	Experimental pan calibrations and construction	37
	3.2.3	Solar irradiated naturally ventilated class A pan (SINVAP)	39
		design	
	3.2.4	Working principle of the SINVAP	43
3.3	Explana	tion of experimental facilities	44
	3.3.1	Experiment setup	44
	3.3.2	Measurement of parameters	50
3.4	Experim	nental procedure	52
	3.4.1	Daily pan evaporation measurement	52
	3.4.2	Meteorological parameters collection	53
	3.4.3	The SINVAP observation	54
3.5	Data ar	nalysis	55
	3.5.1	Validation of evaporation models	55
	3.5.2	Influence of solar irradiated natural ventilation on	56
		evaporation	
	3.5.3	Effect of wire mesh on the evaporation	56
3.6	Calcula	tion procedure	56
	3.6.1	Net incident solar radiation	56
	3.6.2	Aerodynamic component	57
	3.6.3	Vapor pressure	57
3.7	Penma	n equation for the SINVAP evaporation	59
	3.7.1	Analysis of the E <sub>radn</sub>	60
	3.7.2	Analysis of the Eaero	60
CHA	PTER 4	EXPERIMENTAL RESULTS AND DISCUSSION	61
4.1	Global	and net radiation results	61
4.2	Vapor	pressure	63
4.3	Air mo	omentum on the free surface of pan water	66
4.4	Heat s	storage in the pan water	69
4.5	Air te	mperature relations	71
4.6	Experimental evaporation results		



CHA	PTER 5	: ANALYSIS OF VENTILATION PERFORMANCE	80		
		AND EVAPORATION MODELS			
5.1	Broad	feature of flow in the SINVAP	80		
	5.1.1	Air flow	80		
	5.1.2	Manipulate of wire mesh on the air flow	81		
	5.1.3	Flow visualization on the free surface of pan water	82		
	5.1.4	Effect of wire on the smoke flow through the SINVAP	86		
5.2	Validity	of evaporation models	88		
5.3	Performance of evaporation models				
5.4	Analysi	s of Penman equation for the SINVAP evaporation	95		
	5.4.1	Comparison of radiative component	95		
	5.4.2	Comparison of aerodynamic component	97		
СНА	PTER 6	CONCLUSION AND RECOMMENDATION	99		
6.1	Conclu	sion	99		
6.2	Recom	mendation	101		
REF	ERENCE	S	102		
APF	ENDICE	S	111		



· · · ·

# LIST OF TABLES

		Page				
Tables 2.1:	ables 2.1: Summary of effect of meteorological factors on evaporation					
Tables 3.1:	Summary of the experimental pan configurations	38				
Tables 3.2:	Summary of the SINVAP configurations	40				
Tables 3.3:	Instruments range and accuracy	46				
Tables 5.1:	Average measured and predicted evaporation flux	92				
Tables 5.2:	Tables 5.2: Statistical summary of the comparison between observed and					
	six different evaporation estimation models bas	ed				
	configuration D evaporation					
Tables 5.3:	Tables 5.3: Statistical summary of the comparison between observed and					
	six different evaporation estimation models bas	sed				
	configuration G evaporation					
Tables 5.4:	Tables 5.4: Statistical summary of the comparison between observed and					
	six different evaporation estimation models bas	sed				
configuration H evaporation						



# LIST OF FIGURES

•

		Page
Figure 1.1:	Flowchart of research activities	5
Figure 2.1:	Schematic diagram of evaporation from free surface of water	10
Figure 2.2:	Energy balance of an evaporation pan	14
Figure 2.3:	Schematic of basic principle of buoyancy driven flow	18
Figure 2.4:	Air movement in the enclosure caused by pressure difference	19
Figure 2.5:	Sketch of cold inflow	20
Figure 2.6:	Smoke tests in the solar chimney for no wire mesh	20
Figure 2.7:	Smoke test in the solar chimney for wire mesh at the top	21
Figure 3.1:	Schematic diagram of the NWS standard class A pan	36
Figure 3.2:	Photograph of the NWS standard class A pan	36
Figure 3.3:	Photograph of the experimental pan set up (Configuration A)	38
Figure 3.4:	Photograph of the experimental pan set up (Configuration C	, 39
	D)	
Figure 3.5:	Isometric views of the SINVAP (Design 1)	40
Figure 3.6:	Schamatic views of the SINVAP setup (Design 2)	41
Figure 3.7:	Photoghaph of the experimental SINVAP (Configuration E)	42
Figure 3.8:	Photoghaph of the experimental SINVAP (Configurations H is	s 43
	on the left and G is on the right)	
Figure 3.9:	Schematic diagram of thermocouple setup at configuration A 8	& 45
	configuration B	
Figure 3.10:	Schematic diagram of thermocouple setup at outlet opening c	of 46
	the SINVAP	
Figure 3.11:	Photograph of wind speed measurement	47
Figure 3.12:	Photograph of the SINVAP inflow measurement	47
Figure 3.13:	Photograph of the CMP3 Pyranometer	48
Figure 3.14:	Photograhp of the eight channel Cole-Purmer data logger with	48
	K-type themocuple	
Figure 3.15:	Photograph of the AT380 Infrared thermometer	49



Figure 3.16:	Photograph of the Mitutovo digital depth gauge	49
Figure 3.17:	Sketch of measurement of water level in the pan	50
Figure 3.18:	Photograph of measurement of pan water level.	51
Figure 3.19:	Daily evaporation observation chart (Sample)	53
Figure 4.1:	Average daily net radiation $(R_n)$ and average daily incident	62
	global radiation ( $R_{loc}$ ) throughout the observation period (26 <sup>th</sup>	
	May to 5 <sup>th</sup> Jul).	
Figure 4.2:	Comparison of net radiation received by the open pan and the	63
5	SINVAP with global incident solar radiation experimental data	
Figure 4.3:	Comparison of mean daily saturated vapor pressure (kPa)	64
2	measured from 8.00 am to 5.00 pm.	
Figure 4.4:	Comparison of mean daily actual vapor pressure (kPa)	64
	measured from 8.00 am to 5.00 pm.	
Figure 4.5:	Comparison of vapor pressure deficit measured from 8.00 am	65
	to 5.00 pm during 26 <sup>th</sup> May to 5 <sup>th</sup> July in 2015	
Figure 4.6:	Relationship of vapor pressure deficit between the SINVAP and	66
	OP observation measured from 8.00am to 5.00pm	
Figure 4.7:	Hourly local air flow velocities over the pan water surface	67
Figure 4.8:	Comparison of daily average air run over the pan water surface	67
	between the open pan and the SINVAP measured at 0.65 m	
	above the ground surface and at the inlet opening of the	
	SINVAP	
Figure 4.9:	Plot of the percentage deviation of air flow through the	68
	SINVAP vs. local wind run	
Figure 4.10:	Daily change of water temperature in the pan	69
Figure 4.11:	Relationship of heat storage between the SINVAP water and	70
	OP water measured from 8.00am to 5.00pm	
Figure 4.12:	Comparison of daily basis heat storage in the pan water	71
	between the SINVAP and the OP	
Figure 4.13:	Comparison of daily maximum air temperature between the	72
	ambient air and air inside the SINVAP	



•

	Figure 4.14:	Comparison of daily minimum air temperature between the	72
		ambient air and air inside the SINVA	
	Figure 4.15:	Comparison of daily mean air temperature between the	73
		ambient air and air inside the SINVAP	
	Figure 4.16:	Relationship of air temperature between air inside the SINVAP	74
		and ambient air	
	Figure 4.17:	Percentage of deviation of air temperature in the SINVAP	74
	Figure 4.18:	Comparison of daily experimental pan evaporation	76
	Figure 4.19:	Comparison of experimental pan evaporation flux	76
	Figure 4.20:	Experimental evaporation deviation between the SINVAP and	77
		OP (Configuration E & F)	
	Figure 4.21:	Comparison of experimental evaporation flux	78
	Figure 4.22:	Relationship of evaporation between the SINVAP and OP	78
		experiment	
÷	Figure 4.23:	Experimental evaporation deviation between the SINVAP and	79
		OP (Configuration G & H)	
	Figure 5.1:	Relationship of the air flow rate with the differential pressure	80
		drop at SINVAP with wire mesh	
	Figure 5.2:	Relationship of the air flow rate with the differential pressure	81
	Figure 5.3:	Relationship of pressure drop across the SINVAP chimney to	82
		configuration G and configuration H	
	Figure 5.4:	Schematic diagram of the different entering point of smoke in	83
		the SINVAP	
	Figure 5.5:	Starting point of smoke generation at point 1 (Inlet of enclosed	83
		pan)	
	Figure 5.6:	Smoke suction from source of smoke through the inlet	84
	Figure 5.7:	Smoke reach at the point 2(front side of pan)	84
	Figure 5.8:	Smoke passing over the free surface of pan water	85
	Figure 5.9:	Smoke entering at point 3 (inlet of the solar chimney).	85
	Figure 5.10:	Side caption of smoke flow test in the SINVAP for no wire	86
		mesh	



- Figure 5.11: Top side caption of smoke flow test in the SINVAP for no wire 87 mesh
- Figure 5.12: Smoke test in the SINVAP for wire mesh at the top of outlet 87 opening
- Figure 5.13: Comparison of evaporation flux between prediction by 88 evaporation model and experimental for configuration D
- Figure 5.14: Comparison of evaporation flux between prediction by 89 evaporation model and experimental for configuration G
- Figure 5.15: Comparison of evaporation flux between prediction by 89 evaporation model and experimental for configuration H
- Figure 5.16: Relationship of evaporation flux between the pan experimental 90 and the models prediction for configuration D
- Figure 5.17: Relationship of evaporation flux between the SINVAP with wire 91 meshes experimental and the models prediction.
- Figure 5.18: Relationship of evaporation flux between the SINVAP without 91 wire meshes experimental and the models prediction.
- Figure 5.19: Comparison of the term  $\Delta/(\Delta+\gamma)$  for different pan setup. 96
- Figure 5.20: Relationship of Penman radiative evaporation (E<sub>radn</sub>) term for 96 different pan setup
- Figure 5.21:Comparison of the term Df(u) for different pan setup.97
- Figure 5.22:Comparison of the term M for different pan setup.98
- Figure 5.23: Relationship of Penman aerodynamic (E<sub>aero</sub>) term for different 98 pan setup



# LIST OF ABBREVIATIONS

SINVAP	-	Solar Irradiated Naturally Ventilated Class A Pan
ОР	-	Open Pan
NWS	-	National Weather Service
f(u)	-	Wind function
CNRS	-	Centre National de la Recherché Scitifique
VDP	-	Vapor Pressure Deficit
RMSE	-	Root Mean Square Error
MBE	-	Mean Bias Error
MSE	-	Mean Square Error
DE	-	Deviation of Evaporation
UMS	-	Universiti Malaysia Sabah



# LIST OF SYMBOLS

R <sub>n</sub>	-	Net radiation (W/m <sup>2</sup> )
<b>R</b> <sub>ns</sub>	-	Net incoming short wave radiation (W/m <sup>2</sup> )
R <sub>nl</sub>	-	Net outgoing long wave radiation (W/m <sup>2</sup> )
E	-	Evaporation flux (kg/m <sup>2</sup> s)
es	-	Saturated air vapor pressure (Pa)
<b>e</b> a	-	Actual air vapor pressure (Pa)
<b>Q</b> <sub>n</sub>	-	Net solar energy (W/m²)
<b>Q</b> h	-	Net sensible heat loss (W/m <sup>2</sup> )
Q <sub>e</sub>	-	Energy used for evaporation (W/m <sup>2</sup> )
<b>∆Q</b>	-	Heat storage in water (W/m <sup>2</sup> )
ΔΡ	-	Differential pressure drop (Pa)
$\Delta P_{st}$	-	Buoyancy or stack pressure (Pa)
Δ <b>P</b> w	-	Wind draft (Pa)
Q	-	Flow rate (m³/s)
Та	-	Ambient air temperature (°C)
<b>T</b> <sub>i</sub>	-	Indoor air temperature (°C)
A	-	Cross sectional area of opening (m <sup>2</sup> )
K	-	Flow resistance coefficient (Dimensionless)
U2, W	-	Wind speed (m/s)
Cd	-	Pressure coefficient (Dimensionless)
Aeff	-	Effective area of opening (m <sup>2</sup> )
h	-	Canopy chimney height (M)
G	-	Gravitational acceleration (m/s <sup>2</sup> )
<b>E</b> pan	-	Pan evaporation (kg/m <sup>2</sup> s)
Ea	-	Aerodynamic function of evaporation (kg/m <sup>2</sup> s)
Pa	-	Atmospheric pressure (Pa)
Τ	-	Mean daily temperature (°C)
R <sub>s</sub>	-	Global solar radiation (W/m <sup>2</sup> )
Ra	-	Extraterrestrial radiation (W/m <sup>2</sup> )



Cr	- Temperature constant (Dimensionless)
Cw	- Wind constant(Dimensionless)
Сн	<ul> <li>Humidity constant (Dimensionless)</li> </ul>
H <sub>m</sub>	- Relative Humidity (%)
Cs	- Sunshine coefficient (Dimensionless)
S	- Sunshine percentage (Dimensionless)
CE	- Elevation coefficient (Dimensionless)
T <sub>dp</sub>	<ul> <li>Dew point temperature (°C)</li> </ul>
V	- Pan cavity volume (m <sup>3</sup> )
D	- Diameter of Pan (mm)
Н	- Depth of Pan (mm)
L	- Plan length of Pan (mm)
Δ	- Slope of saturated vapor pressure vs temperature curve
	(Pa/°C)
γ	<ul> <li>Psychrometric constant (Pa/°C)</li> </ul>
Λ	<ul> <li>Latent heat of vaporization (J/kg)</li> </ul>
ρ	<ul> <li>ambient air density(kgm<sup>-3</sup>)</li> </ul>
ρι	- Indoor air density (kgm <sup>-3</sup> )



.

•

# LIST OF APPENDICES

		Page
APPENDIX A:	Solar sunshine hour at latitude 6.0367° N	111
APPENDIX B:	Meteorological climates	113
APPENDIX C:	Observation charts	117
APPENDIX D:	Experimental results	125
APPENDIX E:	Parameters of evaporation model	129
APPENDIX F:	Characteristics of evaporation	134
APPENDIX G:	Behavior of Pan Insulation	152
APPENDIX H:	List of Publications	154



#### **CHAPTER 1**

#### INTRODUCTION

This thesis presents a research of open water surface evaporation represented by pan evaporation, and assessment of different evaporation estimation methods that have been used for many years.

This thesis proposes using the principle of natural ventilation to provide enhanced air flow over a square pan by using enhancing chimney made in the vertical duct in East Malaysia. The goal of the thesis is to explore a method to enhance the evaporation rate by utilized solar energy for commercialization of pond natural evaporation system in many fields such as water removal from industrial effluent, brine distillation, salt cultivation, food processing and drying, microalgae drying, evaporative cooling, mining, etc.

There have been many experimental studies completed worldwide, featuring open water surface evaporation. Historically, many cases where the natural evaporation has been used there are required to operate at higher evaporation rate. Natural evaporation can be enhanced by changing the meteorological climates; those are the elements of evaporation function. According to Liu and Xia (2012), the rate of natural evaporation is more responsive to net radiation, followed by relative humidity, air temperature and air flow over the free surface of the water body. Chu et al.; (2012a) showed the draft was enhanced through the natural draft solar chimney by installing wire mesh on the chimney exit to impede cold inflow. The area of this study is to use the enhanced natural draft that is shown Chu et al. in 2012 for increasing evaporation rate.





Literature searches were conducted to survey on open water surface evaporation, standard pan evaporation, measurements of flow into the solar irradiated natural ventilation system were made, and different evaporation estimation models evaluated. Through analysis and experimental studies, the possibility of designing a solar irradiated naturally ventilated class A pan model with higher rates of evaporation was evaluated.

#### 1.1 Research Questions

- a. Are existing equations for estimating the natural water evaporation from class A pan applicable to the Malaysian climate?
- b. Do existing equations for estimating the natural water evaporation rate from class A pan applies to pan modified by a canopy ventilator acting as a chimney?
- c. What are the effects of the pan shape and size on the water evaporate?
- d. Is the draft enhancement found in the modified chimney system reported by Chu, Rahman and Kumaresan (2012a) using air as the working fluid applied to the evaporation system?

#### **1.2** Statement of Research Problem

Class A pan have been the general adoption of direct measurement of natural evaporation rate. The alternative to direct measurement has been greatly influenced by the availability of data of evaporation functions elements. The evaporation from a free water surface is determined using the existing equations that originated from ecological and environmental studies would unlikely be suited for designing pan evaporation rates. However, the pan evaporation rate is little higher than the pond natural evaporation rates (Gundalia and Dholakia, 2013). Therefore, those responsible for estimating daily evaporation are still faced with a bewildering array of calculation methods, many of which give small, but significant between the experimental and predicted evaporation by evaporation models in the final calculated value. The key problem of this study with choosing evaporation models of prediction of evaporation at the Solar Irradiated Naturally Ventilated Class A Pan (SINVAP). Because, the available daily natural evaporation rate



measurement equations does not account for predicting evaporation from the SINVAP.

Pan evaporation data is useful information for estimating water vapor flux from lakes, reservoirs and other water bodies. It can be affected by global and net solar radiation, vapor pressure, air velocity, relative humidity, rainfall, water temperatures, and air temperatures in obtaining the evaporation rate. The combinations of natural air ventilation with open water surface evaporation, using direct irradiated solar energy with other effects has to investigate because, the canopied ventilation that refers to the natural draft enhancement by installing a wire mesh on a solar chimney have been evaluated the flow rate only.

Chu et al. (2012b) concluded that the higher rate of air velocity over the pan water surface can generate such a wave in the pan and splash water out of the pan in several minutes. The splash loss increases as the air velocity increase, with the loss rate at least one order of magnitude greater than the evaporation rate. The important question, is whether the proposed SINVAP that is based on the enhanced natural draft work shown by Chu et al. (2012a) able to produce a splash effect on the pan water?

#### 1.3 Scope of Research

As indicated previously, there has been very little research or basic data collected on evaporation rates under the natural ventilation system. These techniques generally require highly specialized measurements of air velocity and vapor pressure gradients and are based on assumptions that would not be expected to be met in the solar irradiated natural ventilation. Due to the many possible complicating factors, it was decided that the present study, being a pilot project for solar irradiated natural ventilated pan evaporation, should be limited to investigating the validity of the more commonly used methods. The first requirement was for adequate reliable basic data. To obtain this data, standard procedures were used to collect data from observations. The research works performed was limited as per list below:



- Abrew, W., 2001. Evaporation estimation for Lake Okeechobee in South Florida, Journal of Irrigation and Drainage Engineering, **127**: 177.
- Ahmed, M., Shayya, W.H., Hoey, D., Mahendran, A., Morris, R., and Al-Handaly, J., 2000. Use of Evaporation Ponds for Brine Disposal in Desalination Plants, Journal of Desalination, **130**: 155-168.
- Ahmed, M., Shayya, W. H., Hoey, D. and Handaly, J., 2001. Brine Disposal from Reverse Osmosis Desalination Plants in Oman and the United Arab Emirates, Journal of Desalination, **133**: 135-147.
- Allen, R. G. and Pruitt, W. O., 1991. FAO-24 reference evapotranspiration factors, Journal of Irrigation and Drainage Engineering, **117**(5): 758-773.
- Allen, R. G., Pereira, L. S., Raes, D. and Smith, M., 1998. Crop evaporation. Guidelines for computing crop water requirements. Food Agricultural Organization. U.N. Irr. Drainage Paper 56.
- Ambrose, R. B. and Roesch, S. E., 1982. Dynamic estuary model performance, ASCE. 108: No. EEI.
- Andreozzi, A., Buonomo B. and Manca O., 2009. Thermal management of a symmetrically heated channel–chimney system. International Journal of Thermal Sciences **48** (3): 475-487.
- Andreozzi, A., Buonomo, B. and Manca, O., 2010. Thermal and fluid dynamic behaviors in symmetrical heated channel-chimney systems. International Journal of Numerical Methods for Heat & Fluid Flow. **20**(7): 811-833.
- Angstrom, A., 1920. Application of heat radiation measurements to the problem of evaporation from lakes and the heat convection at their surfaces, Geogr. Ann. Heft. **3**: 26

Awbi, H. B., 1991. Ventilation of Buildings, 33, ISBN 0-419-15690-9, E&FN SPON.

Budyko, M. I., 1971. Climate and LiJe. (In Russian.) Hydrometeoizdat, Leningrad. Climate and Lve, Academic Press.

ななののでないたちまたいとれ

Brutsaert, W.H., 1982. Evaporation into the Atmosphere. Reidel, Amsterdam, 299 pp.



- Burman, R. and Pochop, L. O., 1994. Evaporation, evapotranspiration and climatic data. In Developments in Atmospheric Science 22. New York. Elsevier Science B.V.
- Burch, G. J., 1979. A weighing system for freely exposed loads. Agriculture and Forest Meteorology. **20**: 489-491.
- Burgess, M. D. and Hanson, C. L., 1981. Automatic Class A pan filling system. Journal of Hydrology. **50**: 389-392
- Boughton, W. C. and McPhee, R.J., 1987. An automatic recording class a pan evapopluviometer for long-term unattended operation. Agricultural and forest meteorology. **41**:21-29
- Barranco, C. R., Balbuena, M. B., Garcia, P. G., and Fernandez, A. G., 2001. Management of Spent Brines or Osmotic Solutions. Journal of Food Engineering. **49**: 237-246.
- Brunt, D., 1932. Notes on radiation in the atmosphere. Quart J Roy Meteorological Society. **58**: 389-420
- Calder, I. R., and Neal, C., 1984. Evaporation from saline lakes: a combination equation approach, Journal of Hydrological Sciences, Vol. **29**, Issue 1, No. 3, pp. 89 97.
- Crago, R., Brutsaert, W., 1996. Daytime evaporation and the self-preservation of the evaporative fraction and the Bowen ratio. Journal of Hydrology. **178**: 241-255.
- Chu, C. M. Rahman, M. M., and Kumaresan, S., 2012a. Effect of Cold Inflow on Chimney Height of Natural Draft Cooling Towers. Nuclear Engineering and Design, Elsevier. 249: 125-131.
- Chu, C. R., Li, M. H., Chang, Y. F., Liu, T. C. and Chen, Y. Y., 2012b. Wind-induced splash in Class A evaporation pan. Journal of Geophysical Research. **117**: D11101.
- Chu C. R., Li, M. H., Chen, Y. Y., Kuo, Y. H., 2010. A wind tunnel experiment on the evaporation rate of Class A evaporation pan. Journal of Hydrology. **381**: 221-224.



- Costola, D. and Etheridge, D.W., 2008. Unsteady natural ventilation at model scaleflow reversal and discharge coefficients of a short stack and an orifice. Building and Environment. **43**: 1491 – 1506
- Cuenca, R. H., 1989. Irrigation System Design: An Engineering Approach. 552 pp., prentice-hall, englewood cliffs, n. j.
- Cheek, A. W. and Lambert, C. F., 1978. Automatic evaporation measurement system (AUTOVAP) development report. Equipment Development Lab., Silver Springs, MD, NOAA Tech. Manual NWS-DEL-17, 15 pp.
- Christiansen, J. E., 1968. Pan evaporation and evaporation climate data. Journal of Irrigation and Drainage Div. Amer. Soc. Civil Eng. No. IR2. 94:243-265.
- Chow, V. T., Maidement, D. R., Mays, L. W., 1988. Applied Hydrology. McGraw Hill Book Co., New York.
- Dingman, S. L., 1994. Physical Hydrology. Prentice Hall, Englewood Cliffs, NJ, 646 pp.
- Doorenbos, J. Pruitt, W.O., 1977. Crop water requirements. FAO Irrigation and Drainage Paper 24, Rome, Italy.
- Dalton, J., 1802. Experimental essays on the constitution of mixed gases; on the force of steam of vapor from waters and other liquids in different temperature, both in a torricellian vacuum and in air on evaporation and on the expansion of gases by heat. Memoirs and proceeding of the Manchester Literary A philosophical Society. **5**: 535-602.
- Ferguson, J., 1952. The rate of natural evaporation from shallow ponds, Australian Journal of Science Resources, No. 5, pp. 315 330.
- Finch, J., Calver, A., 2008. Methods for the quantification of evaporation from lakes. (Prepared for the World Meteorological Organization's Commission for Hydrology). Oxfordshire, UK, 41 pp.
- Frecks, G. A., Gilbert, C. B. and Thompson, T. L., 1973. Instrumentation for monitoring small weight changes. Trans. ASAE, **16**: 728-830
- Gay, L. W., 1991. Enhancement of evaporation by advection in arid regions from Hydrological interactions between atmosphere, soil and vegetation: Proceedings of the Vienna Symposium.



- Gan, G. and Riffat S. B., 1998. A numerical study of solar chimney for natural ventilation of building with heat recovery. Applied Thermal Engineering.
   18(12): 1171-1187
- Goyal, R. K., 2004. Sensitivity of evapotranspiration to global warming: a case study of arid zone of Rajasthan (India). Agr. Water manage; **69**:1-11.
- Glater, J. and Y. Cohen, 2003. Brine Disposal from Land Based Membrane Desalination Plants: A Critical Assessment. Los Angeles, Polymer and Separations Research Laboratory University of California: 1-16.
- Gilron, J., 2004. Enhanced Evaporation For Treatment of Desalination Brines, The Middle East Desalination Research Center Muscat, Sultanate of Oman.
- Gilron, J., Folkman, Y. Savliev, R., Waisman, M. and Kedem, O., 2003. WAIV-Wind Aided Intensified Evaporation for Reduction of Desalination Brine. **158**: 205-214.
- Gentine, P., Entekhabi, D., Chehbouni, A., Boulet, G., Duchemin, B., 2007. Analysis of evaporative fraction diurnal behavior. Agricultural and Forest Meteorology. **143**: 13 29.
- Hargreaves, G. H., Samani, Z. A., 1985. Reference crop evapotranspiration from temperature. Appl. Eng. Agric. **1**(2): 96-99.
- Hunt, G. R. & Linden, P. F., 1999. The fluid mechanics of natural ventilationdisplacement ventilation by buoyancy-driven flows assisted by wind. Building Environ. **36**: 707-720.
- Hounam, C. E., 1973. Comparison between pan and lake evaporation, World Meteorological Organization Technical Note.**126**: 52 pp.
- Hostetler, S and Radke, B., 1995. An inventory of saline water disposal basins, Murray Basin, AGSO Record 94/4, Australia Geological Survey Organisation, Canberra, Australia.
- Irmak, S., Haman, D. Z. and Jones, J. W., 2002. Evaluation of Class A pan coefficients for estimating reference evapotranspiration in humid location. Journal of Irrigation and Drainage Engineering. **128**(3):153-159
- Jensen, M.E., 1974. Consumptive use of Water and Irrigation Water Requirements. Rept. Tech. Com. on Irrig. Water Req., Irrig. and Drain. Div., Am. Soc. Civ. Engr, 229 p.



- Jensen, M. E., Burman, R. D and Allen R. G., 1990. Evapotranspiration and irrigation water requirements. Amer. Soc. Civil Eng. (New York) Manual Rpt. Eng. Practices No. 70.
- Jhajharia, D., Agrawal, G., Sevda, M. S., 2009. Influence of Meteorological Parameters on Pan Evaporation at Agartala. Journal of Agric. Eng. **46**(1).
- Jobson, W. E., 1980. Thermal modeling of flow in the San Diego Aqueduct, California, and its relation to evaporation. U.S. Geological Survey Professional Paper 1122.24 pp.
- Jackman, A. P., and Yotsukura, N., 1977. Thermal loading of natural streams: U.S. Geol. Survey Prof. Paper 991, 39p.
- Karunanithi, N., Grenney, W.J., Whitley, D., Bovee, K., 1994. Neural networks for river flow prediction. Journal of Computing in Civil Engineering 8(2): 201-220.
- Kohler, M. A. Nordenson, T. J. and Fox. W. E., 1955. Evaporation from pans and lakes. U.S. Dept. Commerce Res. Paper 38.
- Kohler, M. A., 1954. Lake and pan evaporation. pp. 127-148, In: Water-Loss Investigations: Lake Hefner Studies, Tech. Rep., Geological Survey Prof. Paper 269: 170 pp.
- Lamb, H. H., 1972. Climate: Present, Past and Future. Vol. 1, Fundamental climate Now, London, Methuen.
- Lamoreux, W. W., 1962. Modern evaporation formula adapted to computer use. Monthly Weather Rev. **90**:26-28.
- Linacre, E.T., 1977. A simple formula for estimating evaporation rates in various climates, using temperature data alone. Agricultural Meteorology **18**(6):409-424
- Linacre, E. T., 1994. Estimating U.S. Class-A pan evaporation from few climate data, Water Int., **19**: 5–14
- Liu, Q., Xia X. H., 2012. Contribution of meteorological variables to changes in potential evaporation in Haihe River Basin, China. Procedia Environmental Sciences **13**: 1836 1845



- Mickley, M, Hamilton, R, Gallegos, L and Truesdall, J., (1993) Membrane Concentration Disposal, American Water Works Association Research Foundation, Denver, CO, USA.
- Montheith, J. L., 1981. Evaporation and surface temperature. Quart J Roy Meteorological Soc. **107**: 1-27.
- Modi, V. and Torrance, K. E., 1987. Experimental and Numerical Studies of Cold Inflow at the Exit of Buoyant Channel Flows. Journal of Heat Transfer. **109**: 692 - 699.
- Fisher, T. S., Torrance, K. E., Sikka, K.K., 1997. Analysis and Optimization of a Natural Draft Heat Sink System. IEEE Transactions on Components, Packaging, and Manufacturing Technology. Part A. **20** (2): 111 - 119.
- Morton, F. I., 1968. Evaporation and climate: a study in cause and effect, Scientific Series No. 4. Inland Water Branch, Department of Energy, Mines and Resources, Ottawa, Canada.
- Manoj, G. J., Dholakia, M. B., 2013. Dependence of evaporation on meteorological variables at daily time-scale and estimation of pan evaporation in Junagadh region American Journal of Eng. Res. **2**(10): 354-362
- Oroud, I.M., 1999. Temperature and evaporation dynamics of saline solutions, Journal of Hydrology, Vol. **226**, pp. 1-10.
- Oren, A., 2009. Microbial diversity and microbial abundance in salt-saturated brines: Why are the waters of hypersaline lakes red? Natural Resources and Environmental **15**(49): 247–255.
- Peng, J., Borsche M., Liu Y., and Loew A., 2013. How representative are instantaneous evaporative fraction measurements of daytime fluxes? Hydrology and Earth Syst. Sci. **17**: 3913–3919
- Pruitt, W.O., 1966. Empirical method of estimating evapotranspiration using primarily evaporation pans. Proc. Conf. Evapotranspiration and its role in water Resources Management. Chicago, Ill. Amer. Soc. Agr. Eng. St. Joseph, Mich.
- Phene, C. J. and Campbell, R.B., 1975. Automating pan evaporation measurements for irrigation control. Agriculture and forest Meteorology. **15**:181-191.



Penman, H. L., 1946. Evaporation in nature. Rep. Prog. Phys., 11: 366-388.

- Penman, H. L., 1948. Natural evaporation from open water, bare soil and grass, Proc. Roy. Soc. Lon., A**193**: 120-145.
- Penman H. L., 1956. Evaporation: An introductory survey. Netherlands Journal of Agricultural Science **4**: 9-29.
- Penman, H. L., 1963. Vegetation and Hydrology. Tech. Common. **53**, Commonwealth Bureau of Soils, Harpenden, England.
- Pruitt, W.O., 1966. Empirical method of estimating evapotranspiration using primarily evaporation pans. Proc. Conf. on Evapotranspiration and its Role in Water Resources Management. Chicago. Dec. Am. Soc. Agr, Engrs., pp. 57-61.
- Pereira, H. C., 1957. Field measurements of water use for irrigation control in Kenya coffee. Journal of Agricultural Science. **49**: 459-66.
- Pereira, A. R., Villanova, N., Pereira, A. S., Baebieri, V. A., 1995. A model for the class A pan coefficient. Agricultural Water Management. **76** : 75–82.
- Rao, P.S., Saraswarthyamma, C. K. and Sethuraj, M. R., 1998. Studies on the relationship between yield and meteorological parameters of para rubber tree (Heveabrasiliensis). Agricultural Forest Meteorology. 903: 235-245.
- Rayner DP., 2007. Wind run changes: the dominant factor affecting pan evaporation trends in Australia. J Climate.**20**:3379-94.
- Roderick, M. L, Rotstayn L. D, Farquhar G. D, Hobbins M. T, 2007.On the attribution of changing pan evaporation. Geophys Res Lett ;34: L17403, doi: 10.1029/2007GL031166.
- Rayner, D. P., 2007. Wind run changes: the dominant factor affecting pan evaporation trends in Australia. J Climate.**20**:3379-94.
- Rohwer, C., 1931. Evaporation from Free Water Surfaces. USDA Tech. Bull. 271. 96 pp.
- Sartori, E., 1999. A Critical Review of Equations Employed for the Calculation of the Evaporation Rate from Free Water Surfaces, Journal of Solar Energy, Vol. 68, No. 1, 77-89.



- Singh, V. P, Xu, C. Y., 1997. Evaluation and generalization of 13 mass-transfer equations for determining free water evaporation. Hydrol Process **11**:311– 323
- Stanhill, G., 2002. Is the class A evaporation pan still the most practical and accurate meteorological method for determining irrigation water requirements? Agriculture and Forest meteorology. **112**: 233-236.
- Sellers, W. D., 1964.Potential evapotranspiration in arid regions. Journal of Applied Meteorology. **3**: 98-104.
- Shuttleworth, W. J., 1993. Evaporation.IN MAIDMENT, D. R. (Ed.) Handbook of Hydrology. New York, McGraw-Hill Inc.
- Snyder, R. L., 1992. Equation for evaporation pan to evapotranspiration conversions. Journal of Irrigation and Drainage Engineering, ASCE. **118** (6): 977-980.
- Stanhill, G., 1962. The use of the Picheevaporimeter in the calculation of evaporation. Quart J. Roy.Meteorol.Soc. **88**:80-82.
- Singh, R. Bishnoi, O. P., Ram, N., 1992. Relationship between evaporation from class A open pan evaporimeter and meteorological parameters at Hisar. Haryana Agri. Univ. J. Res. **22**(2):97-98.
- Smith, K., Lavis, M. E., 1975. Environmental influences on the temperature of a small upland stream. Oikos **26**(2): 228-236.
- Tanji, K., Ford, S., Toto, A., Summers, J., and Willardson, L., 1993. Management of Irrigation and Drainage Systems: Integrated Perspectives, ASCE, New York, Davis CA, USA.
- Thom, A. S., Thony, J. L, Vauclin, M., 1981. On the proper employment of evaporation pans and atmometers in estimating potential transpiration. Quart. J Roy Met. Soc. **107**: 711-736.
- Thornthwaite, C. W., 1948. An approach towards a rational classification of climate. Geogr. Revue, 38.
- Turc, L., 1961. Evaluation of irrigation water requirements and potential evaporation. annals agronomic **12**, 13-49



- Van W. D. B., 1983. Continuous recording of evaporation from a type A pan. Water South Africa. **9**: 159-162.
- Wallace, J. S., 1995. Calculating evaporation: resistance to factors. Agricultural and Forest Meteorology. **73**: 353-366.
- Watson, I., Burnett, A.D., 1995. Hydrology: An environmental approach. CRC Press, Boca Raton, FL.
- Xiaomang L, Yuzhou L, Dan Z, Minghua Z, Changming L., 2011. Recent changes in pan-evaporation dynamics in China. Geophys. Res. Lett. **38**(13)
- Young A. A., 1945. Euaporation Investigations in Southern California, U. S. Department of Agriculture, Soil Conscrvation Scrvicc, Division of Irrigation.

